

1. KEY FEATURES OF SWITCHING MODE POWER SUPPLY APA1215W

- 1.1. Advanced Technology SMPS Design based on LNK Series by Power Integrations
- 1.2. EcoSmart® Technology built in the IC to provide extremely energy efficient performance
- 1.3. Standby power consumption <50mW
- 1.4. Temperature sensing for thermal protection

2. MECHANICAL

- 2.1. Dimensions: 77mm(L) X 50mm(W) X 67mm(H – Incl. pin)
- 2.2. Weight: Approx. 150gms (without packing)
- 2.3. Connectors:
 - AC Input (Mains Supply): 3 Pin mounted on cabinet
 - DC Output (CPE Side): L-Type Barrel (5.4mm OD; 2.1mm ID)

3. TECHNICAL SPECIFICATIONS

- 3.1. Input Specifications:
 - Input operating range: 90 – 280Vac
 - Operating Frequency: 50Hz
 - Input current with load: 100mA
 - Line Regulation: +/-1.0%
- 3.2. Output Specifications:
 - Output Voltage: 12Vdc
 - Output Current: 1.5Amp
 - Ripple Voltage(pk to pk) <120mV
 - Load Regulation: +/-1.0%
 - Power ON indicator: Red LED

3.3. Environmental:

- Operating Temperature: 0-50 °C
- Storage Temperature: -15 °C to 70 °C
- Humidity: 5% to 95% non-condensing

3.4. Protections:

- Output Over Load Protection: At 10% overload or more, the output will fold back and will resume normal operation on removal of over load
- Output Short Circuit Protection: In case of short circuit, the output will fold back and will resume operation on removal of short
- Over Temperature Protection: In case of temperature exceeding 140 °C at the device, the power supply will shut down and resume normal operation on restoration within normal operating temperature

4. Image of Power Supply Unit:



AXIS POWER TECHNOLOGIES

C 309, Sector 10

NOIDA, U.P. 201301

P: 0120 434 8080/9090

M: +91 981 098 6052

Email: care@axispowertech.com

NOTE: Specifications are subject to change without any prior notification. Image is representation purpose only.